

REQUEST FOR ACCESS OF ABANDONED APPLICATION UNDER 37 CFR 1.14(a)

In re Application of

Application Number

Filed

07/337566

4-13-89

Group Art Unit

Examiner

233

E/M01

Paper No.

24

Assistant Commissioner for Patents
Washington, DC 20231

I hereby request access under 37 CFR 1.14(a)(3)(iv) to the application file record of the above-identified ABANDONED application, which is: (CHECK ONE)

(A) referred to in United States Patent Number 5602987, column _____

(B) referred to in an application that is open to public inspection as set forth in 37 CFR 1.11, i.e., Application No. _____, filed _____, on page _____ of paper number _____

(C) an application that claims the benefit of the filing date of an application that is open to public inspection, i.e., Application No. _____, filed _____, or

(D) an application in which the applicant has filed an authorization to lay open the complete application to the public.

Please direct any correspondence concerning this request to the following address:

Suny Vans

Signature

10-23-97

Date

Suny Vans

Typed or printed name

| | |
|---------------------------------|--|
| FOR PTO USE ONLY | |
| PROCESSED BY | |
| Approved by: <u>OCT 23 1997</u> | |
| (Initials) | |
| Unit: <u>FII</u> | |



US005602987A

United States Patent [19]
Harari et al.

[11] Patent Number: **5,602,987**
[45] Date of Patent: **Feb. 11, 1997**

[54] **FLASH EEPROM SYSTEM**

[75] Inventors: Eliyahou Harari, Los Gatos; Robert D. Norman, San Jose; Sanjay Mehrotra, Milpitas, all of Calif.

[73] Assignee: SanDisk Corporation, Sunnyvale, Calif.

[21] Appl. No.: 174,768

[22] Filed: **Dec. 29, 1993**

- **Related U.S. Application Data**

[60] Continuation of Ser. No. 963,838, Oct. 20, 1992, Pat. No. 5,297,148, which is a division of Ser. No. 337,566, Apr. 13, 1989, abandoned.

[51] Int. Cl. ^d **G06F 11/00**

[52] U.S. Cl. **395/182.06; 365/200; 365/210; 395/427**

[58] Field of Search **371/10.2, 10.3, 371/40.1; 365/200, 185.09, 201, 189.07; 395/575, 182.03, 182.04, 182.05, 182.06, 427, 430**

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,633,475 1/1972 Harper 395/435
4,051,354 9/1977 Choate 365/200
4,093,985 6/1978 Das 395/185.02

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

61 557723 1/1987 Australia .
26 0086886 8/1983 European Pat. Off. .
25 0220718 5/1987 European Pat. Off. .
15 0243503 11/1987 European Pat. Off. .
0300264 1/1989 European Pat. Off. .
58-215794 12/1983 Japan .
66-273795- 12/1983 Japan .
39-45695 3/1984 Japan .
59-1622962 9/1984 Japan .
60-076097 4/1985 Japan .
60-273900 10/1985 Japan .

60178564 2/1986 Japan .
61-96598 5/1986 Japan .
62-283486 12/1987 Japan .
62-283497 12/1987 Japan .
62-1183700 7/1988 Japan .
63-1034545 3/1989 Japan .
21368992 9/1984 United Kingdom .
WO8400628 2/1984 WOPO .

OTHER PUBLICATIONS

Miller, "Semidisk Disk Emulator," *Interface Age*, p. 102, Nov., 1982.

Clewitt, "Bubble Memories as a Floppy Disk Replacement," *1978 Midcon Technical Papers*, vol. 2, pp. 1-7, Dec. 1978.

Hancock, "Architecting a CCD Replacement for the IBM 2305 Fixed Head Disk Drive," *Eighteenth IEEE Computer Society International Conference*, pp. 182-184, 1979.

Wilson, "1-Mbit flash memories seek their role in system design," *Computer Design*, vol. 28, No. 5, pp. 30-32, (Mar. 1989).

(List continued on next page.)

Primary Examiner—Robert W. Beausoliel, Jr.

Assistant Examiner—Ly V. Hua

Attorney, Agent, or Firm—Majestic, Parsons, Siebert & Hsu

[57]

ABSTRACT

A system of Flash EEPROM memory chips with controlling circuits serves as non-volatile memory such as that provided by magnetic disk drives. Improvements include selective multiple sector erase, in which any combinations of Flash sectors may be erased together. Selective sectors among the selected combination may also be de-selected during the erase operation. Another improvement is the ability to remap and replace defective cells with substitute cells. The remapping is performed automatically as soon as a defective cell is detected. When the number of defects in a Flash sector becomes large, the whole sector is remapped. Yet another improvement is the use of a write cache to reduce the number of writes to the Flash EEPROM memory, thereby minimizing the stress to the device from undergoing too many write/erase cycling.

50 Claims, 5 Drawing Sheets

